

Specification



Pixel pitch (mm)	0.62mm	0.78mm	0.93mm	1.25mm	1.5mm	1.87mm
LED Package	COB	COB	COB	COB	COB	COB
Brightness(nits)	600/1000 nits	600/1000 nits	600/1000 nits	600/1000 nits	600/1000 nits	600/1000 nits
Viewing Angle(H/V)	160°/160°	160°/160°	160°/160°	160°/160°	160°/160°	160°/160°
Pixel Density(m2)	2560,000/m2	1638,400/m2	1137,777/m2	640,000/m2	409,600/m2	284,444/m2
Refresh Rate(HZ)	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz
Frame rate	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz
Color temperature	3000k-9300K	3000k-9300K	3000k-9300K	3000k-9300K	3000k-9300K	3000k-9300K
Unit size	600x337.5x75mm	600x337.5x75mm	600x337.5x75mm	600x337.5x75mm	600x337.5x75mm	600x337.5x75mm
Unit size	23.6" x 13.26" x 1.55"	23.6" x 13.26" x 1.55"	23.6" x 13.26" x 1.55"	23.6" x 13.26" x 1.55"	23.6" x 13.26" x 1.55"	23.6" x 13.26" x 1.55"
Unit weight	4kg / 8.8 lbs	4kg / 8.8 lbs	4kg / 8.8 lbs	4kg / 8.8 lbs	4kg / 8.8 lbs	4kg / 8.8 lbs
Power Con(Max/panel)	95w/m²	85w/m²	75w/m²	70w/m²	70w/m²	65w/m²
Input Voltage(AC)	110V / 240V, 50/60 HZ	110V / 240V, 50/60 HZ	110V / 240V, 50/60 HZ	110V / 240V, 50/60 HZ	110V / 240V, 50/60 HZ	110V / 240V, 50/60 HZ
Working temperature	-10°~40°C/10%-90%RH	-10°~40°C/10%-90%RH	-10°~40°C/10%-90%RH	-10°~40°C/10%-90%RH	-10°~40°C/10%-90%RH	-10°~40°C/10%-90%RH
IP Rating	IP54/IP31	IP54/IP31	IP54/IP31	IP54/IP31	IP54/IP31	IP54/IP31
Lifespan	100,000 hrs	100,000 hrs	100,000 hrs	100,000 hrs	100,000 hrs	100,000 hrs
Warranty	24 months	24 months	24 months	24 months	24 months	24 months